



Color Copy coated glossy has a coating specially adapted to digital colour laser printing with a unique gloss effect. It is especially suitable for leaflets, annual reports and brochures.



Technical Data: Color Copy coated glossy

			135		170	200	250
Grammage	g/m²	ISO 536	135	± 3.0	170 ± 4.0	200 ± 6.0	250 ± 8.0
Caliper	mm/1000	ISO 534	106	± 4	135 ± 6	162 ± 7	213 ± 9
Opacity	%	ISO 2471	min 94.0		min 96.0	min 98.0	min 99.0
Moisture	%	ISO 287	4.5	± 0.6	4.8 ± 0.6	4.8 ± 0.6	4.8 ± 0.6
Brightness with UV	D65 %	ISO 2470	102.0	± 2.0	102.0 ± 2.0	102.0 ± 2.0	102.0 ± 2.0
CIE Whiteness*)		ISO 11475	139	± 2.5	139 ± 2.5	139 ± 2.5	139 ± 2.5
Gloss 75°		TAPPI T 48	78	± 4	78 ± 4	78 ± 4	78 ± 4
Formation	Techpap		max 30		max 30	max 30	max 30

Product meets EN 12281, requirements for copy paper for dry toner imaging processes and ISO 9706, requirements for permanence for paper. Production processes certified according to ISO 9001.

SIGNIFICANCE OF VALUES: 2 SIGMA

TECHNICAL CUSTOMER SERVICE 01/07/2009